



garland  
cables

pro series

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

# Security Cable


## Part No: MC146GY

|                       |  |
|-----------------------|--|
| Description           | Stranded 21 AWG (7/0.2mm) PACW, 6Cores, PVC Insulation, PVC Sheath.  |
| Applicable Standards  | AS/CA S-008, BS4737-3.30, AS 1049  |
| Suitable Applications | For inter-connecting wiring, suitable for use in Security/Intruded Alarm system; Use in low voltage/low current applications such as intercommunication.<br><br>Not suitable for mains connection. |

### Cable Construction Drawing



### Cable Construction Relative Parts



### Cable Description

| Conductor  | AWG   | Stranding | Area(mm <sup>2</sup> )       | Diameter(mm) | Material |
|------------|---|-----------|------------------------------|--------------|----------|
|            | 21  | 14/0.2    | 0.44                         | 0.87         | PACW     |
| Insulation | Cores : 6                                       |           | Material : PVC               |              |          |
|            | Colour : White, Blue, Red, Black, Yellow, Green |           | Nominal Thickness (mm) : 0.3 |              |          |
|            | Nominal OD (mm) : 1.5                           |           |                              |              |          |
| Sheath     | Material : PVC                                  |           | Colour : Grey (RAL 7046)     |              |          |
|            | Nominal Thickness (mm) : 0.65                   |           | Nominal OD (mm) : 6.1        |              |          |

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99  
[www.madisontech.com.au/garland](http://www.madisontech.com.au/garland)

made by





garland  
cables

pro series

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.


### Electrical Properties

|                                     |                |
|-------------------------------------|----------------|
| Voltage Rating                      | ELV            |
| Max. Conductor DC Resistance @ 20°C | 45.2Ω/km       |
| Min. Insulation Resistance @ 20°C   | 50MΩ.km        |
| Voltage Test: Conductor to core     | 1.5 kV ac/1min |
| Voltage Test: Core to sheath        | 3.0 kV ac/1min |

### Mechanical Properties

|                                  |             |
|----------------------------------|-------------|
| Operating Temperature Range      | -15 to 70°C |
| Max. Recommended Pulling Tension | 166N        |
| Min. Bend Radius (install)       | 61mm        |
| Approximate Mass                 | 5.47kg/100m |

Sheath Printing

 GARLAND SECURITY CABLE MC146 - 6 x 14/0.2  
22AWG - MM/YYYY - "Mmark"

### Supply Information

| Pack Size | Pack Type    | Dimensions      | Qty Per Carton | Cartons Per Pallet |
|-----------|--------------|-----------------|----------------|--------------------|
| 100m      | Plastic Reel | 10 x 4.5 x 4.5" | 4R             |                    |

| Document Change Record | Issue | Date       | Prepared by | Approved By |
|------------------------|-------|------------|-------------|-------------|
|                        | 01    | 24-11-2012 | LLS         | Pent        |
| Change History         | Issue | Change     |             |             |
|                        |       |            |             |             |

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99  
[www.madisontech.com.au/garland](http://www.madisontech.com.au/garland)

made by

