



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Part No: MC147SHF


| Description | Stranded 21AWG (14/0.2mm) PACW, 7C, PVC Insulation, Aluminium Polyester Tape Overall Screen, 24AWG TACW (7/0.2mm) Drain Wire, LSHF Sheath. |
|-----------------------|--|
| Applicable Standards | AS/CA S-008, BS4737-3.30, AS 1049, EIA RS 232-C |
| Suitable Applications | For inter-connecting wiring, suitable for use in Security/Intruded Alarm systems and low bit rate unbalanced data systems such as RS-232. Can be used to interconnect DTE such as printers, fax machines and modems to consoles; Use in low voltage/low current applications such as intercommunication. |

Not suitable for mains connection.

Cable Construction Drawing



Cable Construction Relative Parts







| Cable Description | | | | | |
|-------------------|---|-----------------|------------------------|----------------|--------------|
| Conductor | AWG | Stranding | Area(mm ²) | Diameter(mm) | Material |
| | 21 | 14/0.2 | 0.44 | 0.87 | PACW |
| Insulation | Cores: 7 Material: PVC Colour: White, Blue, Red, Black, Yellow, Green, Brown Nominal Thickness (mm): 0.3 Nominal OD (mm): 1.5 | | | | Green, Brown |
| Screen | Material | : Al. Polyester | Таре | Coverage: 100% | |

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

| Drain Wire | AWG | Stranding | Area(mm ²) | Diameter(mm) | Material |
|------------|--|-----------|------------------------|--------------|----------|
| | 24 | 7/0.2 | 0.22 | 0.6 | TACW |
| Sheath | Material: LSHF Colour: Grey Nominal Thickness (mm): 0.75 Nominal OD (mm): 6.55 | | | | |

| ELV |
|----------------|
| 45.2Ω/km |
| 50MΩ.km |
| 1.5 kV ac/1min |
| 3.0 kV ac/1min |
| |
| |

| Mechanical Properties | |
|----------------------------------|--|
| Operating Temperature Range | -15 to 70°C |
| Max. Recommended Pulling Tension | 215N |
| Min. Bend Radius (install) | 65.5mm |
| Approximate Mass | 7.0kg/100m |
| Sheath Printing | GARLAND SECURITY CABLE MC147SHF - 7 X 14/0.20 22AWG OAS LSZH - MM/YYYY - "Mmark" |

| Supply Information | | | | | |
|--------------------|-------------|--------------|----------------|--------------------|--|
| Pack Size | Pack Type | Dimensions | Qty Per Carton | Cartons Per Pallet | |
| 500m | Wooden Reel | W39 x 21.8cm | 1R | | |

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

| Document Change Record | Issue | Date | Prepared by | Approved By |
|------------------------|-------|------------|-------------|-------------|
| | 01 | 27-11-2012 | LLS | Pent |
| Characa History | Issue | Change | | |
| Change History | | | | |

With Garland, you are always well connected.

